

Class GSResponse PHP

Description

Wraps Gigya server's response.

Method Summary

Method	Description
GSOBJECT getData()	Returns the response data. Please refer to the REST API reference , for a list of response data structure per me Note: If the request was sent with the <i>format</i> parameter set to "xml", the <i>getData()</i> will return null and you should SObject if the request format is "json" which is the default.
integer getErrorCode()	Returns the result code of the operation. Code '0' indicates success, any other number indicates failure. For cor
string getErrorMessage()	Returns a short textual description of an error, associated with the <i>errorCode</i> , for logging purposes.
string getLog()	Returns a log of the operation for debugging purpose. The format of the log is: <pre>apiMethod=getUserInfo apiKey=2_Y82PzwJ_chSFImHXaIdJcInLyJzmk-VFOa params={"format":"json","uid":"_gid_cZmpLPCjVNRUnm2TH1cwn"} URL=http://socialize.gigya.com/socialize.getUserInfo postData=apiKey=2_Y82PzwJ_chSFImHXaIdJcInLyJzmk-VFOa&format=json&nonce=1286812741402&sig=nr server=web508 response={ "errorCode": 403005, "errorMessage": "Unauthorized user", "statusCode": 403, "statusReason": "Forbidden", "callId": "d8b041336e354a789553830705203779" }</pre>
string getResponseText()	The raw response data. The raw response data is in JSON format, by default. If the request was sent with the <i>fr</i>
integer getInt(string \$key [, integer \$defaultValue])	Type specific methods for retrieving value by key. If the key is not found, and there is no default value, the meth
long getLong(string \$key [, long \$defaultValue])	
Boolean getBool(string \$key [, boolean \$defaultValue])	
string getString(string \$key [, string \$defaultValue])	
GSOBJECT getObject(string \$key)	
GSEArray getArray(string \$key)	